



Care and Use of Hook'em Nets


Hook'em nets are proudly designed and made in Australia...to last. Each unit is fully serviceable with the "NET" being replaceable, ensuring years of service from the handle and frame. Each net hoop and handle are detachable allowing interchangeable options and sizes as you required. We also have a wide range of spares, if you loose a part, or need to make a repairs. No other net on the market can do that.

Replacing The Netting




1) Using a 3mm Allen Key, undo the M6 grub screw on the top of the hoop junction. Be gentle, as the grub screw has been applied with Loctite from the factory to ensure it doesn't loosen with vibrations while in the boat.

Note: Lefty Loosy - Righty Tightly when undoing and tightening the grub screw!!!



2) After loosening the grub screw 3 or 4 turns the hoop tube should release from the hoop junction.

3) Remove the old netting and replace with a fresh unit. This can take a few minutes for some netting types. Ensure you do not unnecessarily bend the hoop out of shape.



4) Once the netting has been fully replaced, carefully take out the grub screw and apply some LOCTITE 222 (low strength).

5) Push the hoop end back into the junction, ensure the hoop is pushed all the way home so the grub screw locates correctly on the corresponding cutout / seat.



6) Tighten up the grub screw. Ensure 'NOT' to over tighten. Over tightening may strip the screw and prevent it from being removed.

7) Pull on the hoop to ensure the grub screw is secured the hoop in place properly.

8) Have 'FUN'. Go and catch some fish.

